



IP Proprietary Telephone

KX-NT556B





The sleek, ultra-modern designed KX-NT556 IP Proprietary Telephone takes you to a new dimension in audio experience through excellent HD quality audio on every phone, combined with easy access to powerful supportive features and applications. A full set of control keys allow access to frequently-used operations such as transferring and conference calling. The Navigator Key provides speed and efficiency when programming names and telephone numbers, searching of quick-dial numbers and accessing many of the system features.

6-Line, 24-Character Graphical Display with Backlight

The LCD displays the various system information such as Caller ID, Date and Time, Call Log, Speed Dialling and Feature menus. The contrast level and back light settings are adjustable to adapt to different lighting conditions. The Multi-Language LCD Support allows the extension users to select from up to the five languages.

36 Self-Labelling Backlit Flexible Outside Line (CO) Keys

Using 3 pages of 12 keys, each extension user can program these 36 keys for various functions such as CO Line appearance, Direct Station Selection (DSS) Key, One-touch Dial or feature setting, all of which help you achieve smoother call handling. The LCD is backlit and each key has a dual colour LED (red/green) that shows information such as line status, extension status or whether a feature is on or off.

Speakerphone with HD Audio

The KX-NT556 is equipped with a full-duplex speakerphone which delivers HD (High Definition) quality audio on every call due to the enhanced echo cancellation and an expanded acoustic chamber.

☞ Headset Jacks

The KX-NT556 provides a 2.5 mm headset jack as well as a 3.5 mm Electronic Hook Switch (EHS) controlled jack for maximum headset flexibility.

Optional CO Key Module

The KX-NT556 can utilize as many as four of the optional 48-button (KX-NT505B) add-on modules that will expand your current 36 flexible CO keys to 84, 132, 180 or 228.

Dual Gbit Ethernet Ports

Dual Gigabit Ethernet ports on the back of the KX-NT556 allows connectivity of the IP Telephone and a computer at a work station that has only a single CAT5 jack (100 Base-T). A built-in Layer 2 switch delivers prioritization of voice over regular data utilizing Quality-of-Service (QoS) through VLAN and Diffserv support.